



Aqua I

Inground Linear



Item Code	550350	550314
Wattage	5W	14W
Beam Angle	12°/24°/36°	12°/24°/36°
Colour Temp.	3000K	3000K
LED lm	280lm	837lm
Dim.(mm)	110 x 280	110 x 350

* Specify for other colour temperatures.



Features:

Slim profile rectangular recessed inground light with options of 5W and 14W LED.

Protection class IP67 with silicone seal.

Extruded aluminium and die cast aluminium housing with high corrosion resistance.

IP67 PG-9 PVC cable gland.

8mm thick tempered high-resolution glass diffuser.

Body frame and the diffuser is aligned to avoid obstruction.

Choice of clear or frosted glass.

316 high grade stainless steel trim.

Choice of 12°/24°/36° beam angles for various illumination applications.

Standard 280mm and 350mm lengths.

3000K colour temperature as standard.

Available colours 3000K, 4000K, 5000K and 6000K optional.

No IR, No Mercury.

50,000 hours long life, low maintenance.

Applications:

Exterior Facade Walls, Building Vicinity, Walkways and Ramps.

Materials/Finish:

Extruded aluminium and die cast aluminium housing with high corrosion resistance, 316 high grade stainless steel trim with 8mm thick tempered glass.


Aqua II

Inground Linear



Item Code	550327	550340
Wattage	27W	40W
Beam Angle	12°/24°/36°	12°/24°/36°
Colour Temp.	3000K	3000K
LED lm	1692lm	2700lm
Dim.(mm)	110 x 650	110 x 920

* Specify for other colour temperatures.



Features:

Slim profile rectangular recessed inground light with options of 27W and 40W LED.

Protection class IP67 with silicone seal.

Extruded aluminium and die cast aluminium housing with high corrosion resistance.

IP67 PG-9 PVC cable gland.

8mm thick tempered high-resolution glass diffuser.

Body frame and the diffuser is aligned to avoid obstruction.

Choice of clear or frosted glass.

316 high grade stainless steel trim.

Choice of 12°/24°/36° beam angles for various illumination applications.

Standard 650mm and 920mm lengths.

3000K colour temperature as standard.

Available colours 3000K, 4000K, 5000K and 6000K optional.

No IR, No Mercury.

50,000 hours long life, low maintenance.

Applications:

Exterior Facade Walls, Building Vicinity, Walkways and Ramps.

Materials/Finish:

Extruded aluminium and die cast aluminium housing with high corrosion resistance, 316 high grade stainless steel trim with 8mm thick tempered glass.