

## Recessed



### Features:

Compact ceiling recessed LED Down Light providing symmetric distribution.

Die cast aluminium luminaire housing.

High purity aluminium reflector.

Frosted UV Stabilised fresnel lens to ensures low glare.

Choice of floating glass.

Wide uniform distribution 65° beam angle.

Colour rendering index: Ra85.

Remote LED driver with male female plug-in for easy installation.

4000K colour temperature as standard.

Available colours 3000K, 4000K, 5000K and 6000K optional.

No IR, No Mercury.

50,000 hours long life, low maintenance.

### Applications:

Residential, Hotels, Offices, Health Sectors, Shopping Malls, Restaurants, Retail Spaces and Public Areas.


### Materials/Finish:

Die cast aluminium body and trim with powder coated paint finish, high quality aluminium reflector complete with UV stabilised frosted UV Stabilised fresnel lens to ensures low glare.

### Specification:

Compact ceiling recessed die-cast aluminium 15W/35W/25W LED Down Light, New generation of LEDs with higher luminaire efficacy CRI 85. High purity aluminium reflector with frosted UV Stabilised fresnel lens to ensures low glare, Wide uniform distribution 65° beam angle.

LED's life 50,000 hours, fixture suitable to operate in -25°C~+40°C ambient temperature.



Item Code	252415	252425	252435
Wattage	15W	25W	35W
Beam Angle	65°	65°	65°
Colour Temp.	4000K	4000K	4000K
LED lm	1600lm	2600lm	3100lm
Dim.(mm)	Φ165 x 95	Φ165 x 95	Φ220 x 110

\* Specify for other colour temperatures.

### Dimming Options:

Leading and trailing edge mains dimmable.

DSI & DALI dimming.

1~10 V dimming.

