


Ceplux SQ Recessed




Item Code	664210	664215	664220	664226
Wattage	10W	15W	20W	26W
Beam Angle	24°/40°	24°/40°	24°/40°	24°/40°
Colour Temp.	4000K	4000K	4000K	4000K
LED lm	731lm	1220lm	1587lm	2135lm
Dim.(mm)	85 x 85	125 x 125	155 x 155	155 x 155


* Specify for other colour temperatures.



70x70mm



110x110mm



140x140mm

Materials/Finish:

Die cast aluminium alloy specially treated non-corrosive body with heat sink fins.

Dimming Options:

Leading and trailing edge mains dimmable.

DSI & DALI dimming.

1~10 V dimming.

Features:

- Recessed square LED Down Light.
- Die cast aluminium luminaire housing and heat sink.
- Specially designed heat sink for better heat management.
- High purity aluminum reflector
- Choice of 24° and 40° beam angles.
- Frosted lens as an option, no glare and wide uniform distribution.
- New generation of COB LEDs with higher efficiency DLOR.
- Colour rendering index: Ra85.

Specially design deep wide trim for glare control.

MacAdam ellipse 2 ensure colour consistency.

4000K colour temperature as standard.

Available colours 3000K, 4000K, 5000K and 6000K optional.

No IR, No Mercury.

50,000 hours long life, low maintenance.

Applications:

Courtyards, Atriums, Hotels, Corridors, Shopping Malls, Educational Facilities, Restaurants, Healthcare, Domestic and Commercial Applications.