


Ceplux Recessed




Item Code	664110	664115	664120	664126
Wattage	10W	15W	20W	26W
Beam Angle	24°/40°	24°/40°	24°/40°	24°/40°
Colour Temp.	4000K	4000K	4000K	4000K
LED lm	731lm	1220lm	1587lm	2135lm
Dim.(mm)	Φ85 x 85	Φ125 x 100	Φ155 x 120	Φ155 x 120

* Specify for other colour temperatures.




Features:

- Recessed circular LED Down Light.
- Die cast aluminium luminaire housing and heat sink.
- Specially designed heat sink for better heat management.
- High purity aluminum reflector.
- Choice of 24° and 40° beam angles.
- Frosted lens as an option, no glare and wide uniform distribution.
- New generation of COB LEDs with higher efficiency DLOR.
- Colour rendering index: Ra85.



- Specially design deep wide trim for glare control.
- MacAdam ellipse 2 ensure colour consistency.
- 4000K colour temperature as standard.
- Available colours 3000K, 4000K, 5000K and 6000K optional.
- No IR, No Mercury.
- 50,000 hours long life, low maintenance.



Applications:

- Courtyards, Atriums, Hotels, Corridors, Shopping Malls, Educational Facilities, Restaurants, Healthcare, Domestic and Commercial Applications.

Materials/Finish:

Die cast aluminium alloy specially treated non-corrosive body with heat sink fins.

Dimming Options:

Leading and trailing edge mains dimmable.
 DSI & DALI dimming.
 1~10 V dimming.