



Mellow Box Recessed



Features:

Body is made of zinc coated sheet steel with a high gloss white epoxy polyester powder paint giving resilient finish.
 Hinged type diffuser for easy maintenance.
 Highly uniform non-glare frosted diffuser for high output technology with large visible area.
 Laser printed PMMA light guide with 95% reflective film.
 Ideal replacement to meet today's energy saving requirements and

mandatory regulations by various authorities.
 Highly bright uniform light output.
 60% energy saving.
 No Maintenance.
 5000K colour temperature as standard.
 Available colours 4000K, 5000K and 6000K optional.
 No IR, No Mercury.
 50,000 hours long life, low maintenance.
 Compatible with various dimming



	CRI 85	Ta 40°C	V 240	IP 40		
--	--------	---------	-------	-------	--	--

Item Code	235018	235042	235056
Wattage	18W	42W	56W
Beam Angle	128°	128°	128°
Colour Temp.	4000K	4000K	4000K
LED lm	1470lm	3470lm	4650lm
Dim.(mm)	300 x 300	600 x 600	300 x 1200

* Specify for other colour temperatures.

control systems and all false ceiling types.
 Optional self contained or central battery emergency lighting versions available on request.

Materials/Finish:
 Body is made of zinc coated sheet steel with a high gloss white epoxy polyester powder paint giving resilient finish with smooth profile, durable UV stabilised diffuser.

Applications:
 Offices, Meeting Rooms, Clean Areas, Hospitals, Laboratories, Banks, Class Rooms and Large Corridors.

Dimming Options:
 DSI & DALI dimming.
 1~10 V dimming.

